

# **Guideline for Dust Suppression**

## **1 Introduction**

- 1.1 Definitions**
- 1.2 Why are Dust Suppressants Used?**
- 1.3 Roles and Responsibilities**

## **2 General Dust Suppression Guidelines**

- 2.1 Notification for Use of Approved Products**
- 2.2 Approved Products**
- 2.3 Application Procedures**
- 2.4 Environmental Concerns**
  - 2.4.1 General**
  - 2.4.2 Water**
- 2.5 Spill Contingency Plan**

## **3 New Products**

- 3.1 Leachate Toxicity Testing**

## **4 Conclusion**

## **5 Bibliography**

## **Appendices**

June 2013

## Guideline for Dust Suppression

### 1 Introduction

The purpose of this guideline is to make you aware of the procedures you must follow before applying a dust suppressant in the Northwest Territories. The Environment Division (ED) of the Department of Environment and Natural Resources (ENR) has currently approved three dust suppressants for use on Commissioner's Land in the NWT. This publication provides guidance for applying these products and a process for approving other dust suppression products.

Section 2.2 of the *Environmental Protection Act* gives the Minister of Environment and Natural Resources the authority to develop, coordinate and administer these guidelines (see Appendix A).

#### 1.1 Definitions

<i>Approved Product</i>	A product approved by ED for dust suppression.
<i>Commissioner's lands</i>	Lands in the NWT that have been transferred by Order-in-Council to the Government of the Northwest Territories. This includes highways, block land transfers and most lands within municipalities.
<i>Leachate Test</i>	Leachate Extraction Procedure - Canadian General Standards Board (CGSB) #164-GP-1-MP (or as amended) or equivalent.
<i>PCB</i>	Polychlorinated biphenyl.
<i>Roadway</i>	The traveled surface of a road, from shoulder to shoulder; it does not include the side slopes or ditches.
<i>Set</i>	The point at which the product becomes stable, according to the manufacturer's specifications.
<i>Used Oil</i>	Any oil from an industrial or non-industrial source that has become unsuitable for its intended purpose due to the presence of impurities or the loss of original properties.

## 1.2 Why are Dust Suppressants Used?

Reasons for using dust suppressants include:

Safety	Untreated roads may lead to more accidents. Accident potential is increased due to loss of visibility.
Health	Dust particles may become a health hazard when they become trapped in the lungs.
Vegetation	Large amounts of dust may induce changes in vegetation due to increased heat absorption and decreased transpiration.
Aquatic Resources	High levels of dustfall into aquatic systems may adversely affect aquatic plants and fish that are not adapted to high levels of sedimentation.
Road Maintenance Costs	Treated roads can lower road maintenance costs by reducing gravel loss and blading time.
Aesthetics	Dust produces an immediate visual impact that may affect residents who live near dust prone roads.

An Ambient Air Quality Guideline established under the *Environmental Protection Act* sets standards respecting the maximum desirable levels of dust in ambient air in the NWT. Measured as total suspended particulate (TSP), the standards for dust over 24 hours are 120 micrograms per cubic metre ( $\mu\text{g}/\text{m}^3$ ) and averaged over a year are 60  $\mu\text{g}/\text{m}^3$ . These standards apply to the whole of the NWT. They define the long term goal for air quality to protect unpolluted parts of the Territory and for the continuing development of control options in polluted areas.

## 1.3 Roles and Responsibilities

Although the *Environmental Protection Act* does not require permits for the application of dust suppressants in the NWT, all suppressants must first be approved by ED. While general conditions are provided for approved dust suppressants, additional conditions may be required on a case by case basis.

The responsible party, being the landowner, road authority or municipal authority, must make provisions to notify the public and contact ENR before applying suppressants. The responsible party must also verify that the products are approved for use and properly applied by the applicator. If the product migrates from the roadway and is deemed to violate the *Environmental Protection Act*, the person(s) responsible must be prepared to take appropriate remedial measures.

Applicators are also accountable for their actions. Applicators are responsible for ensuring that the product is approved for use in the NWT, is correctly applied to the designated area and does not migrate off the site. Applicators, manufacturers and retailers must provide information about new products to ED for approval before their use in the NWT (section 3).

***It is important to remember that the responsible party (the landowner, road authority or municipal authority) is liable for any activity they authorize. Contamination of the environment and subsequent remediation of the site is ultimately their responsibility (see Appendix A).***

## 2 General Dust Suppression Guidelines

There are many aspects to consider before you apply a dust suppressant in the NWT. The following are general guidelines to be followed:

### 2.1 Notification for Use of Approved Products

The following parties must be notified:

Property Owner	Any application of a dust suppressant should be conducted according to an agreement between the applicator and the responsible road authority or property owner. A written agreement is recommended.
ENR	Before any application, provide the local Renewable Resource Officer with the following information: the location of the site, the product(s) used and a timetable for the work.
Public	Notify the affected public before any application. This can be through signs, public notices or media announcements.

### 2.2 Approved Products

Calcium chloride and DL10 are currently the only approved dust suppressants in the NWT. Appendix B contains a list of approved products and information regarding the application of these products.

Other products cannot be used in the NWT until they have been approved by ED.

***Used oil cannot be used as a dust suppression/road stabilizing product or added to other dust suppression products.***

### 2.3 Application Procedures

Directions	Follow the manufacturer's specifications or other tested and approved procedures.
Roadway	The application shall be limited to the roadway, driveway or parking lot.
Rate	Carefully monitor the application rate to ensure adequate coverage without pooling or runoff of products.  The amount of dust suppressant applied should not exceed the minimum amount required to effectively suppress dust.

Incorporation	Products must be bladed or incorporated into the road immediately upon application, to ensure the product does not migrate off the roadway.
Surplus	There should be no evidence of excess product on the roadway.
Migration	The material must not migrate or run off the traveled portion of the roadway.

## **2.4 Environmental Concerns**

### **2.4.1 General**

Contaminants	Dust suppressants must conform with the manufacturer's specifications and must not contain concentrations of contaminants that would not normally be found in the suppressant.
PCB Concentration	Materials that contain more than 2 parts per million (ppm) of PCB are considered unacceptable and shall not be applied as a dust suppressant.

### **2.4.2 Water**

Proximity to Water	Ensure that dust suppressants do not enter and contaminate waterbodies, including surface and groundwater. Do not allow the product to leave the roadway.
Sensitive Environments	Application rates near sensitive environments, (e.g. marshes), must be closely monitored. Remember, environmental restoration is the responsibility of the landowner, road authority or municipal authority.
Flooding	Do not apply products to areas of roads that are subject to flooding.
Imminent Precipitation	Do not apply products if precipitation is occurring, or forecast to occur before the product sets or cures.

## 2.5 Spill Contingency Plan

Provide EPS with a contingency plan, if required by the *Spill Contingency Planning and Reporting Regulations*, under the *Environmental Protection Act*.

Be prepared to respond to spills, including any product that migrates off the roadway.

## 3 New Products

Products that have not been approved by ED must undergo an assessment before being approved for use as a dust suppressant. The following information is required before such an assessment can be done:

Manufacturer's Information	Manufacturer's specifications and application procedures.
Laboratory Analysis	All new products must be characterized by an accredited laboratory.
Material Safety Data Sheets (MSDS)	Complete Workplace Hazardous Material Information System (WHMIS) data sheets.
Toxicity Tests	Toxicity tests should be provided for LC-50 and LD-50.
Leachate Tests	(see section 3.1)
Other Requirements	<p>Provide a proposed schedule of field tests to confirm product efficiency and appropriate application rates.</p> <p>Provide any other materials, tests or analysis carried out on the substance.</p> <p>Provide copies of approvals from other jurisdictions.</p> <p>Laboratory or testing costs are the responsibility of the person(s) applying for approval.</p>

### 3.1 Leachate Toxicity Testing

New, non-approved dust suppressant products may be required to undergo the leachate extraction procedure to determine toxicity of the product. Testing should be carried out on a sample consisting of the material, at the standard application

rate, and on a representative sample of road material. Such a leachate toxicity test can be undertaken by a variety of reputable commercial laboratories. Leachate extraction procedure CGSB #164-GP-1-MP, or an acceptable equivalent, must be used (see Appendix C).

## **4 Conclusion**

This is a brief introduction to dust suppressant application in the NWT.

For more information, please contact:

Environment Division  
Environment and Natural Resources  
600, 5102-50 Avenue  
Yellowknife, NT, X1A 3S8  
phone (867) 873-7654 fax (867) 873-0221

***Remember that this document is to inform you of the procedures you must follow before applying dust suppressants in the NWT. If you have any questions or comments, contact the Environment 8 j j g j c b before beginning a dust control program.***



## 5 Bibliography

Community Dust Control Program - Technical Services Division. Calcium Chloride as a Dust Suppressant. Department of Government Services and Public Works, Yellowknife, N.W.T., (1992).

Environmental Protection Act - Spill Contingency Planning and Reporting Regulations.

Gazette officielle du Quebec. Environmental Quality Act - Hazardous Waste Regulation- Schedules III and IV. Quebec: Editeur officiel du Quebec, (1988).

Government of British Columbia. British Columbia Waste Management Act - Special Waste Regulation, Schedule 4, Queen's Printer of British Columbia, (1988).

Government of Ontario. Regulation 347 (formerly Reg. 309) -Schedule 4, Toronto, Ontario: Queen's Printer of Ontario, (1980).

Green, L. Public Awareness Information for Dust Control on N.W.T. Highways, Yellowknife, N.W.T.: Department of Transportation, (1992).

RTAC●ARTC Guidelines for Cost Effective Use and Application of Dust Palliatives, (1987).

Ontario Ministry of the Environment. Draft Guidelines for the Application of Product Dust Suppressant Materials, Toronto, Ontario: Ontario Ministry of the Environment, (1992).

Secretary of Canadian General Standards Board(CGSB). Leachate Extraction Procedure 164-GP-IMP, Ottawa, Ontario: CGSB, (1987).

Techman Engineering Ltd. Road Dust Suppression in Northern and Western Canada- Manual or Recommended Procedures, Calgary, Alberta: Environment Canada, (1982).

Thompson, N. Use of Entac Dust Suppressant, Yellowknife, N.W.T.: Environmental Protection Division, Renewable Resources Department, (1990).

# Appendix A

## ***Environmental Protection Act***

The following is a subset of the *Environmental Protection Act*. The complete act can be obtained from the Environmental Protection Service, Department of Resources, Wildlife and Economic Development.

1. In this Act,

"contaminant" means any noise, heat, vibration or substance and includes such other substance as the Minister may prescribe that, where discharged into the environment,

- (a) endangers the health, safety or welfare of persons,
- (b) interferes or is likely to interfere with normal enjoyment of life or property,
- (c) endangers the health of animal life, or
- (d) causes or is likely to cause damage to plant life or to property;

"discharge" includes, but not so as to limit the meaning, any pumping, pouring, throwing, dumping, emitting, burning, spraying, spreading, leaking, spilling, or escaping;

"environment" means the components of the Earth and includes

- (a) air, land and water,
- (b) all layers of the atmosphere,
- (c) all organic and inorganic matter and living organisms, and
- (d) the interacting natural systems that include components referred to in paragraphs (a) to (c).

2.2. The Minister may

- (a) establish, operate and maintain stations to monitor the quality of the environment in the Territories;
- (b) conduct research studies, conferences and training programs relating to contaminants and to the preservation, protection or enhancement of the environment;
- (c) develop, co-ordinate and administer policies, standards, guidelines and codes of practice relating to the preservation, protection or enhancement of the environment.

5. (1) Subject to subsection (3), no person shall discharge or permit the discharge of a contaminant into the environment.

(2) **REPEALED.** R.S.N.W.T. 1988,c.117(Supp.),s.8.

(3) Subsections (1) does not apply where the person who discharged the contaminant or permitted the discharge of the contaminant establishes that

- (a) the discharge is authorized by this Act or the regulations or by an order issued under this Act or the regulations;
- (b) the contaminant has been used solely for domestic purposes and was discharged from within a dwelling-house;
- (c) the contaminant was discharged from the exhaust system of a vehicle;
- (d) the discharge of the contaminant resulted from the burning of leaves, foliage, wood, crops or stubble for domestic or agricultural purposes;
- (e) the discharge of the contaminant resulted from burning for land clearing or land grading;
- (f) the discharge of the contaminant resulted from a fire set by a public official for habitat management of silviculture purposes;

- (g) the contaminant was discharged for the purposes of combating a forest fire;
- (h) the contaminant is a soil particle or grit discharged in the course of agriculture or horticulture; or
- (I) the contaminant is a pesticide classified and labeled as "domestic" under the *Pest Control Products Regulations* (Canada).

(4) The exceptions set out in subsection (3) do not apply where a person discharges a contaminant that the inspector has reasonable grounds to believe is not usually associated with a discharge from the excepted activity. R.S.N.W.T. 1988,c.75(Supp.),s.5;c.117(Supp.),s.8.

- 5.1 Where a discharge of a contaminant into the environment in contravention of this Act or the regulations or the provisions of a permit or licence issued under this Act or the regulations occurs or a reasonable likelihood of such a discharge exists, every person causing or contributing to the discharge or increasing the likelihood of such a discharge, and the owner or the person in charge, management or control of the contaminant before its discharge or likely discharge, shall immediately
  - (a) subject to any regulations, report the discharge or likely discharge to the person or office designated by the regulations;
  - (b) take all reasonable measures consistent with public safety to stop the discharge, repair any damage caused by the discharge and prevent or eliminate any danger to life, health, property or the environment that results or may be reasonably expected to result from the discharge or likely discharge; and
  - (c) make a reasonable effort to notify every member of the public who may be adversely affected by the discharge or likely discharge. R.S.N.W.T. 1988,c.75(Supp.),s.5; c.117(Supp.),s.9.
6. (1) Where an inspector believes on reasonable grounds that a discharge of a contaminant in contravention of this Act or the regulations or a provision of a permit or licence issued under this Act or the regulations has occurred or is occurring, the inspector may issue an order requiring any person causing or contributing to the discharge or the owner or the person in charge, management or control of the contaminant to stop the discharge by the date named in the order.
7. (1) Notwithstanding section 6, where a person discharges or permits the discharge of a contaminant into the environment, an inspector may order that person to repair or remedy any injury or damage to the environment that results from the discharge.
 

(2) Where a person fails or neglects to repair or remedy any injury or damage to the environment in accordance with an order made under subsection (1) or where immediate remedial measures are required to protect the environment, the Chief Environmental Protection Officer may cause to be carried out the measures that he or she considers necessary to repair or remedy an injury or damage to the environment that results from any discharge.

## Appendix B

### Approved Dust Suppression Products and Application Information

#### Calcium Chloride

This is a commonly used product in the NWT. It is available in granular and liquid form. Because it is hygroscopic and deliquescent, it draws moisture from the air and will control dust if applied frequently enough.

Road surface conditions and traffic volume dictate the amount, timing and frequency of calcium chloride application. With normal application procedures and concentrations, it is generally non-toxic with rapid dissolution in the environment. However, calcium chloride can wash away in heavy rain. For more information read: *Calcium Chloride as a Dust Suppressant*, (see section 5).

Toxicity to Plants	Calcium chloride is toxic to some plants. Keep the product on the roadway.
Application Rate	Apply minimum amounts as it can cause roads to become slippery.
Applicator Competence	Ensure application personnel are informed of corrosive nature of the product (can be harmful to eyes and skin with direct contact).
General Guidelines	Follow all other general dust suppressant guidelines listed in section 2.

## **Appendix B (cont'd.)**

### **DL10**

DL10 is an asphalt product that is mixed with water and a soap solution. DL10 should be applied to one side of the road at a time, and then allowed to set for approximately three hours. Braking may be difficult on freshly treated road, so a pilot car may be necessary to direct traffic during the application. Vehicles should travel no faster than 20 km/hr through areas where the application has not set.

Fresh DL10 can be washed off using soap and water. If it is allowed to dry, a solvent may be required.

General Guidelines    Follow all general dust suppressant guidelines listed in section 2.

## Appendix C

**Leachate Extraction Procedure Test and Equivalents** (see bibliography section for complete documentation).

The Environment Division may require new products to undergo the following test:

CGSB #164-GP-1-MP Leachate Extraction Procedure Canadian General Standards Board (or as amended).

Or one of these equivalent tests:

Schedules III and IV - Environmental Quality Act - Hazardous Waste Regulation-  
Gazette officielle du Quebec.

Schedule 4 - British Columbia Waste Management Act - Special Waste Regulation,  
Government of British Columbia.

Schedule 4 - Regulation 347 (formerly Reg. 309), Government of Ontario.

If you would like to be placed on a mailing list to receive guideline amendments or for public consultation on Environment Division legislation please fill this out and mail or fax to:

Environment Division  
Department of Environment and Natural Resources  
Government of the Northwest Territories  
600, 5102 - 50th Avenue  
Yellowknife, NT, X1A 3S8  
Fax: (867) 873-0221

Mailing List for Environmental Protection Service Information

Name: \_\_\_\_\_

Title: \_\_\_\_\_

Address: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Phone/Fax Number \_\_\_\_\_